



**Technical information**

**CF1<sup>®</sup>**  
**ReadyMix**



**Technical Data**

Density at 20°C	1,0680 g/cm <sup>3</sup>
Viscosity at 20°C	2,3 mPas
PH- value at 20°C	9,5 at 30g/l
Boiling temperature	100°C
Explosion risk	none
Solubility in water	unlimited
Application temperature	20 - 45°C
Application	pure
Storing frost-free	in original container
Disposal by EAK no.	07 06 99
WPC	1
Hazards identification	no marking required

CF1 maintenance oven cleaner is a water based alkaline cleaning ReadyMix for manual cleaning e.g. by spraying and after a short soaking period wiping with a cloth

Cleans colophonium and flux quickly, thoroughly and with best possible product protection e.g. from machinery parts, solder frames, carriers, aluminium, GRP, PVCs, stainless steel, glass etc. without rinsing.

In case of hard and old contamination please use the product Kolb G50, Part No. 090620

**Applications**

Cleaning of:	
Low VOC flux	++*
Colophonium flux	++*
Waterbased flux	++*
Solder paste (soldered)	++*
Machine parts, plastics	++*

**Please be aware: The product may irritate mucuous membrane, skin and eyes!**  
**For commercial use only!**

**Your CF1 supplier:**

**Process**

	Manual cleaning

**Part No. 090618 // PU: 15 x 1000 ml**

**Part No. 090618-10 // Contents: 10l**

**Made in Germany**

**Part No. 090618-25 // Contents: 25l**

**\*++ = ideal for application, + = recommended, o = usable but not recommended, - = not recommended**  
**Note:** The spreadsheet only shows a general overview of the cleaning media specifications. Rinsing with tap water with a too high lime concentration may cause lime residues after drying. Cleaning tests are reasonable and necessary to determine the optimum cleaner configuration. Such tests may be carried out directly at the **kolb** Demonstration Center in Willich / Germany or can be initiated by contacting one of our international subsidiaries.

**Kolb Cleaning Technology GmbH**  
Karl-Arnold-Str. 12 · D - 47877 Willich  
Further information: [www.kolb-ct.com](http://www.kolb-ct.com)

Phone +49 (0) 2154 9479 - 38  
Fax +49 (0) 2154 9479 - 47  
e-mail [info@kolb-ct.com](mailto:info@kolb-ct.com)

All modifications due to technical improvements are subject to change without notice.